

mMESH™ 2W Commander Node

Product Datasheet M-CMDR-2



Image above is for illustration purpose.



RF Specifications

Waveform	COFDM
Frequency Range	
M-CMDR-2-110150	1100 - 1500MHz
Carrier Bandwidth	
Narrow Band	0.25 / 0.5 / 1MHz
Wide Band	1.25 / 2.5 / 5 / 10 / 20MHz
Max Throughput	
Narrow Band	940Kbps
Wide Band	100Mbps
RF Output	2W
Carrier Modulation	QPSK / 16QAM / 64QAM / 256QAM / 1024QAM
FEC Rate	FEC 1/3, 2/3
Receive Sensitivity	-100dBm @ 5MHz
RF Interface	2x N-Type (2x Tx, 2x Rx)



Power

Power Input	100 - 240 VAC 28 - 36 VDC
Power Consumption (Max)	30W



Streaming

Streaming Protocol	UDP, RTSP, RTP
--------------------	----------------



Networking

Ethernet	10 / 100Mbps
WIFI	2.4 / 5 GHz



Audio

Audio Codec	Adaptive Multi-Rate (AMR)
Data Bitrate	4.8Kbps



I / O

2x Ethernet Port



Security

Data Encryption	DES / AES 128 / AES 256
-----------------	-------------------------



Physical

Dimensions (L x W x H)	502 x 415 x 246mm
Weight	~11Kg (Varies between setup)



Environment

Operating Temperature	-20 to 50°C
-----------------------	-------------

* T.B.C. / Under Development

For more information on Licenses and Features, please contact your local salesperson.